

**SERIES
8110S**

Power and Control Tray Cable, TC-ER-HL/CIC/MTW/WTTC/AWM

Direct Burial, Sun Res, Hazardous Locations

Fixed application, shielded



Use

Shielded UL Listed cables built for the uses specified by ANSI/NFPA 79, by Art. 336, 392, 501 of ANSI/NFPA 70 "National Electrical Code" (NEC) and by CSA C22.1 (CE Code). For applications in Hazardous Locations, the TC-ER version is suitable for use in Class I, Division 2 while the TC-ER-HL* version is suitable for use in Class I, Division 1. The cables identified with Type TC-ER (Exposed Run) can be installed in the industrial plants for the connections between the cable trays and the equipment without the employment of metal conduits or reinforced cables MC type (Metal Clad Cable); this type of connection is called Open Wiring. The TC-ER / MTW type cables must comply with the impact resistance requirements required for MC type cables, they are oil resistant, sun resistant and can be used in the presence of humidity also buried (they are certified Direct Burial according UL 1277). These cables are also certified Flexible Motor Supply Cable for variable speed drives and Wind Turbine Tray Cable (WTTC) for wind turbine applications where they are able to withstand the torsional stresses due to the loop between the nacelle and the tower.

Information. An additional UL certified cut-to-length service is carried out on request ("Processed Wire").

* Important. The TC-ER-HL version for installations in Hazardous Locations Class I, Division 1 is upon specific request.

Technical data

Characteristics	Value/property
Conductor	Flexible copper strand, class 5
Insulation	TKblend®-R
Conductor distinction	Black numbered + yellow/green (beginning from 3 conductors)
Fillers	Central or side fillers, if any
Shield	Gray version: Tinned copper braid, nom. coverage 85% Black version: Aluminum/polyester + Tinned copper braid, nom. coverage 85%
Jacket	PVC compound, oil-resistant, RAL 7001 gray color or black color. Metric marking.
Temperature range	+90°C (dry conditions), +75°C (wet conditions) -40°C (fixed); -5°C (not fixed)
Voltage rating	600 V (TC/CIC/MTW), 1000 V (AWM/WTTC), 600/1000 V (IEC)
Spark test	6000 V
Bending radius	6 x cable outer diameter (20 x cable outer diameter for non-cyclical mobile uses)
Torsion movements	±150° / 1 m
Standards of construction	UL/CSA approvals: (UL) Type TC-ER-HL (18 AWG-1000 kcmil), MTW, WTTC, Dir Bur, Sun Res, Oil Res I, Oil Res II, c(UL) TC-ER (18 AWG-1000 kcmil), CIC (18 AWG-4/0 AWG), Dir Bur, Sun Res, Oil Res, Type TW75 (≥14 AWG), cURus AWM Style 21179, AWM I/II A/B; Class 1, Div.1* or Div.2 NEC Art. 336, 392, 501; CSA C22.1 Tab.19; UL 1581, UL 758, UL 1277, UL 1063, UL 2277, UL 2225, CSA C22.2 No.230-09 e No. 239-09 Flame res.: FT1, FT4, IEC 60332-1-2, IEC 60332-3-24 UV res.: UNI EN ISO 4892-3 (gray), UNI EN ISO 4892-2 (black) Other: Low Voltage Directive (LVD) 2014/35/EU
Standards of use	NFPA 79, NFPA 70 (NEC), UL 508a, CSA C22.1 (CE Code), CSA C22.2 No.286, Style 21179

Marking

TEKIMA 8110S – CE 4G2,5 mm² (UL) E361258 TC-ER-HL4x14 AWG DIR BUR SUN RES OIL RES 600V THHW 90°C Dry / 75°C Wet FT4/IEEE 1202 or WTTC or FLEXIBLE MOTOR SUPPLY CABLE 1000V 90°C Dry or MTW 600V or AWM 21179 90°C 1000V c(UL) CONTROL CABLE CIC/TC-ER DIR BUR SUN RES OIL RES 600V 90°C Dry / 75°C Wet PVC TW75 SHIELDED FT4 or AWM I/II A/B 90°C 1000V FT1 14 AWG – (prod.reference) = (metric) =

Coding and dimensions

Code	Number of conductors	Size [AWG/kcmil]	Size [mm ²]	Diameter [mm (inch)]	Weight [kg/km (lb/mft)]
CV02X100_8110S_□□**	2	18	1	8,5 (0.335)	100 (67)
CV02X150_8110S_□□**	2	16	1,5	9,2 (0.362)	122 (82)
CV02X250_8110S_□□**	2	14	2,5	10,0 (0.394)	156 (105)
CV03G100_8110S_□□	3	18	1	8,9 (0.350)	120 (81)
CV03G150_8110S_□□	3	16	1,5	9,7 (0.382)	144 (97)
CV03X150_8110S_□□	3	16	1,5	9,7 (0.382)	144 (97)
CV03G250_8110S_□□	3	14	2,5	10,5 (0.413)	188 (127)
CV03G400_8110S_□□	3	12	4	11,9 (0.469)	256 (172)

Code	Number of conductors	Size [AWG/kcmil]	Size [mm ²]	Diameter [mm (inch)]	Weight [kg/km (lb/mft)]
CV03G600_8110S_□□	3	10	6	13,9 (0.545)	354 (238)
CV03GB25_8110S_□□	3	4	25	25,6 (1.008)	1185 (796)
CV03GB50_8110S_□□	3	1	50	34,1 (1.343)	2190 (1472)
CV03GX30_8110S_□□	3	300	152	52,7 (2.075)	5813 (3906)
CV04G100_8110S_□□	4	18	1	9,7 (0.382)	143 (96)
CV04G150_8110S_□□	4	16	1,5	10,5 (0.413)	182 (122)
CV04G250_8110S_□□	4	14	2,5	11,4 (0.449)	240 (161)
CV04G400_8110S_□□	4	12	4	13,0 (0.512)	330 (222)
CV04G600_8110S_□□	4	10	6	15,3 (0.600)	475 (319)
CV04GB10_8110S_□□	4	8	10	19,4 (0.762)	766 (515)
CV04GB16_8110S_□□	4	6	16	24,6 (0.969)	1201 (807)
CV04GB25_8110S_□□	4	4	25	28,1 (1.106)	1694 (1138)
CV04GW03_8110S_□□	4	3	26,7	31,1 (1.224)	1904 (1279)
CV04GB35_8110S_□□	4	2	35	31,0 (1.220)	2202 (1480)
CV04GB50_8110S_□□	4	1	50	37,7 (1.484)	3204 (2153)
CV04GW/1_8110S_□□	4	1/0	53,5	39,2 (1.543)	3149 (2116)
CV04GB70_8110S_□□	4	2/0	70	44,2 (1.740)	4397 (2955)
CV04GB95_8110S_□□	4	3/0	95	47,7 (1.878)	5566 (3740)
CV04GL12_8110S_□□	4	4/0	120	50,3 (1.980)	6652 (4470)
CV04GL15_8110S_□□	4	250	150	55,9 (2.201)	7564 (5083)
CV04GX30_8110S_□□	4	300	152	58,1 (2.287)	7837 (5266)
CV04GL18_8110S_□□	4	350	185	60,0 (2.362)	8953 (6016)
CV04GX50_8110S_□□	4	500	254	73,1 (2.878)	12413 (8341)
CV05G100_8110S_□□	5	18	1	10,5 (0.413)	172 (116)
CV05G150_8110S_□□	5	16	1,5	11,4 (0.449)	216 (145)
CV05G250_8110S_□□	5	14	2,5	12,5 (0.492)	286 (192)
CV05G400_8110S_□□	5	12	4	15,2 (0.596)	434 (291)
CV05G600_8110S_□□	5	10	6	16,7 (0.656)	569 (382)
CV05GB10_8110S_□□	5	8	10	22,4 (0.882)	957 (643)
CV05GB16_8110S_□□	5	6	16	27,1 (1.067)	1445 (971)
CV05GB25_8110S_□□	5	4	25	31,1 (1.224)	2059 (1383)
CV07G100_8110S_□□	7	18	1	11,4 (0.449)	210 (141)
CV07G150_8110S_□□	7	16	1,5	12,4 (0.488)	267 (179)
CV07G250_8110S_□□	7	14	2,5	14,6 (0.573)	386 (259)
CV07G400_8110S_□□	7	12	4	16,5 (0.648)	545 (366)
CV08G100_8110S_□□	8	18	1	13,9 (0.545)	276 (185)
CV08G150_8110S_□□	8	16	1,5	15,4 (0.604)	370 (249)
CV09G100_8110S_□□	9	18	1	14,7 (0.579)	303 (204)
CV09G150_8110S_□□	9	16	1,5	15,0 (0.591)	357 (240)
CV09G250_8110S_□□	9	14	2,5	17,3 (0.681)	476 (320)
CV09G600_8110S_□□	9	10	6	23,0 (0.906)	983 (661)
CV12G100_8110S_□□	12	18	1	15,5 (0.608)	348 (234)
CV12G150_8110S_□□	12	16	1,5	16,9 (0.663)	447 (300)
CV12G250_8110S_□□	12	14	2,5	18,5 (0.726)	605 (407)
CV12G400_8110S_□□	12	12	4	22,0 (0.866)	858 (577)
CV12G600_8110S_□□	12	10	6	24,2 (0.953)	1134 (762)
CV18G100_8110S_□□	18	18	1	17,9 (0.703)	483 (325)
CV18G150_8110S_□□	18	16	1,5	19,6 (0.770)	626 (421)
CV18G250_8110S_□□	18	14	2,5	22,6 (0.890)	847 (569)
CV18G400_8110S_□□	18	12	4	25,5 (1.004)	1201 (807)
CV18G600_8110S_□□	18	10	6	28,2 (1.110)	1592 (1070)
CV25G100_8110S_□□	25	18	1	20,3 (0.797)	606 (407)
CV25G150_8110S_□□	25	16	1,5	23,4 (0.921)	767 (515)
CV25G250_8110S_□□	25	14	2,5	25,4 (1.000)	1132 (761)
CV25G400_8110S_□□	25	12	4	29,1 (1.146)	1597 (1073)
CV25G600_8110S_□□	25	10	6	32,5 (1.280)	2175 (1462)
CV33G150_8110S_□□	33	16	1,5	26,0 (1.024)	1185 (796)
CV34G100_8110S_□□	34	18	1	24,6 (0.969)	883 (593)
CV34G150_8110S_□□	34	16	1,5	26,6 (1.047)	1100 (739)
CV41G100_8110S_□□	41	18	1	26,3 (1.035)	1024 (688)
CV41G150_8110S_□□	41	16	1,5	28,5 (1.122)	1276 (857)

Code	Number of conductors	Size [AWG/kcmil]	Size [mm ²]	Diameter [mm (inch)]	Weight [kg/km (lb/mft)]
CV50G100_8110S_□□	50	18	1	28,4 (1.118)	1196 (804)
CV50G150_8110S_□□	50	16	1,5	31,0 (1.220)	1545 (1038)
CV61G100_8110S_□□	61	18	1	30,1 (1.185)	1404 (943)
CV61G150_8110S_□□	61	16	1,5	33,0 (1.299)	1826 (1227)

** According to NFPA 70 (NEC) and CSA C22.1 (CEC) cables with 2 conductors are not Exposed Run (ER).

Code composition

