

Spine

Plugs

Attachment Plugs, Fuseless



Impiego - Use




Spine prodotte a specifiche NEMA e caratterizzate da un'elevata durabilità, resistenza all'impatto e agli agenti chimici. I morsetti di cablaggio consentono di collegare un'ampia gamma di conduttori e il morsetto di compressione della guaina permette di evitare le sollecitazioni di trazione sui singoli conduttori. Queste prese rispondono ai requisiti dell'articolo 406 del ANSI/NFPA 70 "National Electrical Code" (NEC) e, su specifica richiesta, sono disponibili in versione "hospital" qualora fosse richiesta la conformità all'articolo 517 del ANSI/NFPA 70 "National Electrical Code" (NEC).

Plugs manufactured according to NEMA specifications and characterized by high durability, impact resistance and chemical agents resistance. The wiring terminals allow a wide range of conductors' sizes and compression terminal of the sheath avoids tensile stresses on the individual conductors. These plugs meet the requirements of Art. 406 of ANSI/NFPA 70 "National Electrical Code" (NEC) and, upon request, are available in "hospital" grade in compliance with Art. 517 of ANSI/NFPA 70 "National Electrical Code" (NEC).


Dati Tecnici - Technical data

Caratteristica - Characteristics	Valore/proprietà - Value/property
Materiale <i>Material</i>	Corpo in Nylon, contatti in ottone, contatto di terra in lega di rame. <i>Housing made of Nylon, contact blades made of brass, ground contact blade made of copper alloy.</i>
Temperatura massima di esercizio <i>Maximum working temperature</i>	+75°C
Temperatura minima di esercizio <i>Minimum working temperature</i>	-40°C (senza sollecitazioni di impatto / without impact)
Grado di protezione <i>Protection class</i>	IP 20
Diametro del cavo <i>Cable diameter</i>	5,8÷18,3 mm (0,23" ÷ 0,72")
Dimensioni conduttori <i>Wire size</i>	18÷10 AWG
Identificazione terminali <i>Terminal identification</i>	Ottone, Argento (Bianco), Verde <i>Brass, Silver (White), Green</i>
Rigidità dielettrica <i>Dielectric voltage</i>	2000 V
Non propagante la fiamma <i>Flame retardant</i>	HB (UL 94)
Riferimenti normativi costruttivi <i>Standards of construction</i>	UL 498
Riferimenti normativi di impiego <i>Standards of use</i>	UL 508A


Codifiche e dimensioni - Coding and dimensions




NEMA 5-15P



NEMA 5-20P



NEMA 6-15P



NEMA 6-20P

Codice <i>Code</i>	N.Poli <i>Wires</i>	Configurazione <i>Configuration</i>	Corrente massima <i>Current rating [A]</i>	Tensione <i>Voltage rating [V]</i>	Classe di potenza <i>Power rating [HP]</i>	Dimensioni - <i>Dimensions</i> [mm (inch)]	
						A	B
CSHBL5266C	2+G	NEMA 5-15P	15	125	0,5	50,0 (1,97")	38,9 (1,53")
CSHBL5366C	2+G	NEMA 5-20P	20	125	1,0	50,0 (1,97")	38,9 (1,53")
CSHBL5666C	2+G	NEMA 6-15P	15	250	1,5	50,0 (1,97")	38,9 (1,53")
CSHBL5466C	2+G	NEMA 6-20P	20	250	2,0	50,0 (1,97")	38,9 (1,53")