

SERIES
N0000

Trecce tonde flessibili in rame rosso e in rame stagnato

Bare or tinned flexible copper braids



Codifiche e dimensioni - Coding and dimensions

Codice <i>Code</i>	Sezione <i>Size [mm²]</i>	Diametro <i>Diameter [mm (inch)]</i>	Filo <i>Wire [mm (inch)]</i>	Peso <i>Weight [kg/km (lb/mft)]</i>	Tipo rame <i>Copper type</i>
CVC600_NR600	6	4,0 (0.157)	0,2 (0.008)	60 (40)	Rosso - Bare
CVCB10_NR600	10	4,5 (0.177)	0,2 (0.008)	100 (67)	Rosso - Bare
CVCB16_NR600	16	5,8 (0.228)	0,2 (0.008)	160 (108)	Rosso - Bare
CVCB25_NR600	25	7,3 (0.287)	0,2 (0.008)	250 (168)	Rosso - Bare
CVCB35_NR600	35	8,2 (0.323)	0,2 (0.008)	350 (235)	Rosso - Bare
CVCB50_NR600	50	9,6 (0.378)	0,2 (0.008)	500 (336)	Rosso - Bare
CVCB75_NR600	75	12,0 (0.472)	0,2 (0.008)	750 (504)	Rosso - Bare
CVCL10_NR600	100	14,0 (0.551)	0,2 (0.008)	1000 (672)	Rosso - Bare
CVC600_NS600	6	4,0 (0.157)	0,2 (0.008)	60 (40)	Stagnato - Tinned
CVCB10_NS600	10	4,5 (0.177)	0,2 (0.008)	100 (67)	Stagnato - Tinned
CVCB16_NS600	16	5,8 (0.228)	0,2 (0.008)	160 (108)	Stagnato - Tinned
CVCB25_NS600	25	7,3 (0.287)	0,2 (0.008)	250 (168)	Stagnato - Tinned
CVCB35_NS600	35	8,2 (0.323)	0,2 (0.008)	350 (235)	Stagnato - Tinned
CVCB50_NS600	50	9,6 (0.378)	0,2 (0.008)	500 (336)	Stagnato - Tinned
CVCB75_NS600	75	12,0 (0.472)	0,2 (0.008)	750 (504)	Stagnato - Tinned
CVCL10_NS600	100	14,0 (0.551)	0,2 (0.008)	1000 (672)	Stagnato - Tinned

Composizione del codice - Code composition

CVC							
Sezione <i>Size</i>	Inserire <i>To be inserted</i>						
1, 1,5, ..., 6 mm²	100, 150, ..., 600						
10, 16, ..., 95 mm²	B10, B16, ..., B95						
100, 120, ..., 240 mm²	L10, L12, ..., L24						

Tipo rame <i>Copper type</i>	Inserire <i>To be inserted</i>
Rosso - Bare	NR600
Stagnato - Tinned	NS600